CRD3101

Cradle for OPR3101

+ Models

CHG3101 Charging

CRD3101 Bluetooth communication, charging

+ Specifications

Communication
- RS232: 600 bps - 57.6 kpbs
- Bluetooth: Ver. 2.0, output power class 2, range up to 10m, 1 to 1 connection, slave mode, authentication and encryption
- USB: Ver. 2.0, client, HID, USB-A connector

Power
- Voltage requirement: 6V ± 5%
- Battery charging time: Max. 5 hours with power supply, max. 10 hours with USB bus power

Durability
- Temperature in operation: 0 to 40 °C / 32 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Humidity in operation: 20 - 85% (non-condensing)
- Humidity in storage: 20 - 90% (non-condensing)

Physical
- Dimensions (w x h x d): 100 x 115 x 185 mm / 3.94 x 4.53 x 7.28 in
- Weight body: Ca. 250 g / 8.8 oz
- Case: ABS, Black or White

Regulatory & Safety
- Product compliance: CE, RoHS

Enclosed items
- USB cable
- RS232 cable
- Power supply 100-240V/0.5A, 50/60 Hz, 6V/2A

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City
- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariong
- **Brazil:** São Paulo

Opticon Sensors Europe B.V
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON

WWW.OPTICON.COM